

Smarter Working Made Simple



TASKalfa 2554ci/3554ci

**Color Multifunction Product
for A4/A3 Format**

TASKalfa 2554ci

1 Plain
A4/2

Main Specifications			
Model	TASKalfa 2554ci		TASKalfa 3554ci
Main Function	Copy, Print, Scan, Fax (Optional)		
Writing Method	Semiconductor Laser		
CPU	ARM A53 1.6GHz		
Print Speed (A4) (Mono/Color)	25/25 ppm		35/35 ppm
Scanning Speed (A4) 300dpi	DP-7140	Simplex	50 ipm
		Duplex	16 ipm
Scanning Speed (A4) 300dpi	DP-7150	Simplex	80 ipm
		Duplex	48 ipm
Scanning Speed (A4) 300dpi Dual Scan	DP-7160	Simplex	100 ipm
		Duplex	200 ipm
Scanning Speed (A4) 300dpi Dual Scan with Duplex Feed Detection DP	DP-7170	Simplex	100 ipm
		Duplex	200 ipm
Memory	Standard 4GB (Max. 4GB)		
SSD/HDD Capacity	SSD 32GB (Standard) / HDD 320GB or 1TB (Optional)		
Stable Time (From the mainpower ON)	18 seconds		
Paper Capacity	Standard	2 x 500 sheets (Cassette) + 150 sheets (MPT) (A4 / Letter size or less equivalent to 80 g/m ²) 2 x 600 sheets (Cassette) + 165 sheets (MPT) (A4 / Letter size or less equivalent to 64 g/m ²)	
	Maximum	7,150 sheets (Main Unit + 2 x 1,500 sheets PF-7150 x1 + 3,000 sheets PF-7120 x1 + MPT)	
Paper Size	Cassette	Min. A6R - Max. SRA3(320mm x 450mm); Cassette 1 Min. A6R - Max. A4R (Legal)	
	MPT	Min. A6R - Max. SRA3(320mm x 450mm) & Banner Print (1,220mm x 304.8mm)	
Paper Weight	Cassette	52-300g/m ²	
	MPT	52-300g/m ² ; Banner paper 136-163g/m ²	
Duplex Printing	Paper size: Min. A6R - Max. SRA3(320mm x 450mm); Paper weight: 60-256g/m ²		
Output Capacity	Max. 500 sheets + 100 sheets face-down with Inner Job Separator		
Control Panel	10.1 inch resistive touch panel		
Dimension (W x D x H) (Main Unit)	602mm x 665mm x 790mm		
Weight (Main Unit)	Approx. 90 kg		
Power Consumption (Standard configuration)	Copy/Print Mode	450W	590W
	Stand-by Mode	40W	
	Energy Saver	0.5W	
Noise (ISO7779 / ISO9296)	Copy/Print Mode (Mono/Color)	66dB/67dB	68dB/69dB
	Stand-by Mode	35dB	
Copy Functions (Standard)			
Copy Size	Max. A3 (Ledger) - Min. A6R (StatementR)		
Resolution	Scanning: 600 x 600 dpi; Writing: 1200 x 1200 dpi multiple value		
First Copy Time (Mono/Color)	6.4/8.5 seconds		5.3/7.0 seconds
Zoom Ratio	Manual	25% - 400% (1% per Step)	
Multiple Copy	1 - 9,999		
Print Functions (Standard)			
Resolution	1,200 x 1,200 dpi; 4,800 equivalent x 1,200 dpi level		
PDL & Emulation	PRESCRIBE, PCL6 (PCL-XL, PCL 5c), KPDL3 (Postscript 3 compatible), XPS, OpenXPS, PDF Direct Print Ver. 2.0		
First Print Out Time (Mono/Color)	7.0/9.2 seconds		5.9/7.7 seconds
Supported Protocol	TCP/IP(IPv4/IPv6), Bonjour		
Operating System Supported	Windows 8.1/10, Windows Server 2012/2012 R2/2016/2019, Mac OS X(10.9-), Google Chrome OS		
Interface	Ethernet (1000Base-T/100Base-TX/10Base-T)x1, USB 3.0x1, USB Host Interface (USB Host)x4, NFC TAGx1		
Scan Functions (Standard)			
Original size	Table: Max. A3 (Ledger) DP: Max. A3 (Ledger) - Min. A6R (DP-7140 is A5R) Banner: Max. 1,900mm		
Resolution	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi, 200 x 100 dpi, 200 x 400 dpi		
File Format	TIFF, JPEG, XPS, OpenXPS, PDF (MMR/JPG compression/High-compression PDF), PDF/A-2, Encrypted PDF, Searchable PDF (Optional), MS Office file(Optional)		
Image Type Mode	Text, Photo, Text + Photo, Text (Fine Line)		
Send Method	SMB (Version 3.0), SMTP, FTP, FTPoverSSL, USB, TWAIN Source (Network), WIA Driver (Network), DFS, DSM		
Address Storage	2,000 addresses (Common address list), 500 groups (Group address list)		
Fax Functions (Optional)			
Original Size	Max. A3 (Ledger) - Min. A6R (StatementR), Banner: 1,600mm		
Coding Method	MMR, MR, MH, JBIG		
Transmission Speed	33.6 kbps		
Transmission Time	Less than 3 sec. (With JBIG)		
Memory	170MB		
Options			
Document Processor	DP-7150: 140 sheets RADF Type; DP-7140: 65 sheets RADF Type (TASKalfa 2554ci / TASKalfa 3554ci only); DP-7160: 320 sheets One-path Duplex Scanning Type; DP-7170: 320 sheets One-path Duplex Scanning Type with double paper feeding detector		
Paper Feeder	PF-7140: 500 sheets x 2; PF-7150: 1,500 sheets x 2 (A4/Letter); PF-7120: 3,000 sheets Large capacity side deck (A4/Letter)		
Finisher	DF-7100: Inner Finisher *No support for 70ppm; AK-7110: Attachment Kit; DF-7120: 1,000 sheets Finisher; DF-7140: 4,000 sheets Finisher with 65 sheets Staple; DF-7150: 4,000 sheets Finisher with 100 sheets Staple; PH-7C: Punch Unit for DF-7120/DF-7140/DF-7150; PH-7120: Punch Unit for DF-7100; MT-730(B): 7 Bin Mailbox for DF-7140; JS-7110: Inner Job Separator; IS-7100*: Inserter Unit; ZF-7100*: Z Folding Unit; BF-730: Booklet Folder for DF-7140; BF-9100: Booklet Folder for DF-7150; SH-10: Staple for DF-7100/DF-7120/BF-730/BF-9100; SH-12: Staple for DF-7140; SH-14: Staple for DF-7150		
Fax System	Fax System 12		
Internet FAX	Internet FAX Kit(A)		
Card Authentication	Card Authentication Kit(B)		
Gigabit Ethernet Board	IB-50		
Wireless LAN Interface	IB-37 (Wi-Fi 2.4 GHz/5 GHz multi-band support) / IB-38 (Wi-Fi 2.4 GHz capable) *IB-38 for Indonesia, Bangladesh only		
Storage Device	HD-15: HDD 320GB, HD-16: HDD 1TB		
Embedded OCR	Scan Extension Kit(A)		
Banner Paper Tray	Banner Guide 10		
Numeric Key Pad	NK-7120		
Original Tray	DT-730 (B)		
Keyboard Holder	Keyboard Holder 10		

KYOCERA Document Solutions Hong Kong Limited

16/F, Mita Centre, 552-566, Castle Peak Road,
Tsuen Wan, N.T., Hong Kong
Tel : +852-3582-4000 / Fax: +852-3185-1399



KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.
© 2021 KYOCERA Document Solutions Hong Kong Limited.

